



NOTE:

1. Data Transfer: Up to 5Gbps(USB3.2 Gen1)
2. Data Transfer: Up to 480Mbps(USB2.0)
3. Output voltages :5V DC.
4. Output current:900mA max. (USB3.2 Gen1)
5. Output current:500mA max. (USB2.0)
6. Operating Temperature:0°C~45°C
7. Storage Temperature:-20°C~70°C
8. RoHS and REACH compliant

MATERIAL LIST:

⑤	MOULD	40P PVC BLACK	2	
④	HOUSING	ALUMINUM GREY	2	
③	CONNECTOR 2	USB2.0*3+USB3.0+PCBA, THE PIN GOLD PLATED, BLUE PBT INSULATION, THE SHELL FOR NICKEL PLATED	1	
②	CONNECTOR 1	USB C/M, BLACK PBT INSULATION, THE PIN GOLD PLATING, THE SHELL FOR NICKEL PLATING	1	
①	CABLE	(32AWG*1P+AL+MY)*2C+32AWG*1P+24AWG*2C+AL PVC/BLACK OD=4.0±0.2mm	L±T	
NO.	PARTS NAME	SPECIFICATION DESCRIPTION	Q'ty	REMARK
		NEW	2022-09-21	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

Desc.	STANDARD USB Type C 4 in 1 Hub, 4x USB AF(1xUSB 3.2 Gen 1+3xUSB 2.0), grey
Item No.	S3017

SECOMP